

# Material Safety Data Sheet

SiGNa™ Na-Silica Gel (Stage II)



## Section 1. Chemical product and company identification

**Common Name:** SiGNa™ Na-Silica Gel (Stage II)

**Material Uses:** Provides a stable powder with more reactive surface area than Na or K alone, but does not react with dry air as does Na metal. Ideal for chemical reactions that need the reducing ability of alkali metals in an easily handled form. Can produce clean hydrogen by reaction with water. Useful for batch, or continuous, reduction of organic and inorganic compounds (Birch and Wurtz reactions, desulfurization, cleavage of functional groups such as C-X, C-S, C=O, etc.)

**Supplier/Manufacturer:** SiGNa Chemistry, Inc., 530 E. 76<sup>th</sup> Street, Suite 9E, New York, NY 10021  
Tel: 1-212-933-4101 Fax: 1-212-208-2605 Email: safety@siganchem.com

**In case of emergency:** 1-888-779-0780

## Section 2. Hazards identification

**Physical State:** Solid (Amorphous solid powder)

**Emergency Overview:** Danger!  
CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS  
SPILLED POWDER WILL REACT SLOWLY WITH HUMID AIR  
CONTACT WITH WATER RELEASES FLAMABLE HYDROGEN GAS  
Do not get in eyes, on skin or clothing. Do not breathe dust. Keep away from heat, sparks, and flame. Will react with water or steam to produce heat and toxic fumes. Keep container closed. Use only with adequate ventilation.

**Routes of entry:** Dermal contact. Eye contact. Inhalation. Ingestion.

**Potential acute health effects:**

Eyes	Corrosive to eyes.
Skin	Corrosive to the skin.
Inhalation	Corrosive to the respiratory system.
Ingestion	May cause burns to mouth, throat and stomach.

**Potential chronic health effects:** CARCINOGENIC EFFECTS: Classified 3 (Not classifiable for human.) by IARC [Synthetic amorphous silica, precipitated].  
MUTAGENIC EFFECTS: Not available.  
TERATOGENIC EFFECTS : Not available.

**Medical Conditions**  
**Aggravated by Exposure:** Repeated exposure of the eyes to a low level of dust can produce eye irritation.  
Repeated skin exposure can produce local skin destruction, or dermatitis.  
Repeated inhalation of dust can produce varying degree of respiratory irritation or lung damage.  
Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

See toxicological information (section 11)

## Section 3. Composition, Information on Ingredients

	CAS number	% by weight
<b>United States</b>		
Synthetic amorphous silica, precipitated	112926-00-8	60-70
Sodium metal	7440-23-5	30-40

This material is classified as hazardous under OSHA regulations

See Chapters 8, 11 and 14 for details.

**Date of issue** : 03/31/2005  
Authored by **KEMIKA**

**Date of Revision** : 11/14/2007

## SiGNa™ NaK-Silica Gel (Stage I)

### Section 4. First aid measures

<b>Eye Contact:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>Skin Contact:</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion:</b>	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
<b>Notes to physician:</b>	No specific antidote. Medical staff must contact Poison Control Center.

### Section 5. Fire fighting measures

<b>Flammability of the product:</b>	Can be ignited with a flame.
<b>Auto-ignition temperature:</b>	The lowest known value is 120 to 125°C (248 to 257°F).
<b>Products of combustion:</b>	Some metallic oxides.
<b>Fire hazards in presence of various substances:</b>	Flammable in presence of open flames, sparks and static discharge. Slightly flammable to flammable in presence of heat.
<b>Fire fighting media and instructions:</b>	Use dry chemical or CO <sub>2</sub> . Do not use water or foam.
<b>Special protective equipment for fire-fighters:</b>	Will react with water or steam to produce heat and hydrogen gas. Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure.

### Section 6. Accidental release measures

<b>Personal Precautions:</b>	Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
<b>Environmental Precautions:</b>	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
<b>Methods for Cleaning Up:</b>	If emergency personnel are unavailable vacuum or carefully scoop up spilled materials and place in an appropriate container for disposal. Avoid creating dusty conditions and prevent wind dispersal.

### Section 7. Handling and storage

<b>Handling:</b>	Do not get in eyes, on skin or on clothing. Keep container closed. Use only with adequate ventilation. Do not breathe dust. Keep away from heat, sparks and flame. Will react with water or steam to produce heat and toxic fumes. Wash thoroughly after handling.
<b>Storage:</b>	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use.

### Section 8. Exposure Controls, Personal Protection

<b>Engineering Controls:</b>	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
------------------------------	---

#### Personal Protection:




Eyes

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.



Recommended: Safety glasses.

## SiGNa™ NaK-Silica Gel (Stage I)

Respiratory	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.	
Hands	Recommended: Dust respirator. Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.	
Skin/Body	>8 hour(s) (breakthrough time): Nitrile gloves. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  Body: Recommended: Lab coat or overall. Feet: Recommended: Shoes	
<b>Personal protection in case of a large spill:</b>	Safety glasses, goggles or face shield. Impervious gloves.	

### Product name United States

Synthetic amorphous silica, precipitated

### Exposure limits

#### ACGIH TLV (United States, 1/2004).

TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Gel

TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: All forms.

#### OSHA PEL 1989 (United States, 3/1989).

TWA: 6 mg/m<sup>3</sup> 8 hour(s). Form: All forms

Consult local authorities for acceptable exposure limits.

## Section 9. Physical and chemical properties

<b>Physical State:</b>	Solid (Amorphous solid powder)
<b>Color:</b>	Brown to black
<b>Specific Gravity:</b>	0.7 (Water = 1)
<b>Vapor Pressure:</b>	0 kPa (0 mm Hg) (at 20°C)
<b>Solubility:</b>	Reacts with water to form hydrogen, metal hydroxide, and sodium silicate

## Section 10. Stability and reactivity

<b>Stability and Reactivity:</b>	The product is stable.
<b>Conditions of Instability:</b>	Very high temperatures or the presence of water and humid air.
<b>Incompatibility with Various Substances:</b>	Reactive or incompatible with liquid water. Reacts with water vapor. Reactive with oxidizing agents, acids. The product reacts with water to emit flammable but non toxic gases.
<b>Hazardous Polymerization:</b>	Will not occur.

## Section 11. Toxicological information

<b>Acute Effects:</b>	
Eyes	Corrosive to the eyes.
Skin	Corrosive to the skin.
Inhalation	Corrosive to the respiratory system.
Ingestion	May cause burns to mouth, throat and stomach.
<b>Potential Chronic Health Effects:</b>	CARCINOGENIC EFFECTS: Classified 3 (Not classifiable for human.) by IARC [Synthetic amorphous silica, precipitated]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.

Date of issue : 03/31/2005  
Authored by KEMIKA

Date of Revision : 11/14/2007

## SiGNa™ NaK-Silica Gel (Stage I)

### Section 12. Ecological information

Products of degradation: Some sodium silicates

### Section 13. Disposal considerations

**Waste Disposal:** The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

### Section 14. Transport information

Classification

DOT/IMDG/IATA:	UN number	Proper shipping name	Class	Packing group
	UN2813	WATER-REACTIVE SOLID, N.O.S. (sodium-potassium alloy)	4.3	II

NAERG: 138

Label:

UN/Other regulations      DOT



Additional Information:

### Section 15. Regulatory information

United States

**HCS Classification**

Water reactive material  
Corrosive material

**U.S. Federal Regulations**

TSCA : All components listed.  
SARA 302/304/311/312 extremely hazardous substances: No products were found.  
SARA 302/304 emergency planning and notification: No products were found.  
SARA 302/304/311/312 hazardous chemicals: Sodium-potassium alloy  
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Sodium-potassium alloy: Fire hazard, reactive, Immediate (Acute) Health Hazard  
Clean Water Act (CWA) 307: No products were found.  
Clean Water Act (CWA) 311: No products were found.  
Clean air act (CAA) 112 accidental release prevention: No products were found.  
Clean air act (CAA) 112 regulated flammable substances: No products were found. Clean air act (CAA) 112 regulated toxic substances: No products were found.  
Pennsylvania RTK: Sodium metal: (generic environmental hazard).  
Massachusetts RTK: Synthetic amorphous silica, precipitated; Sodium metal.  
New Jersey: Sodium metal.

**State Regulations**

**International Regulations:**

**International lists**

Australia (NICNAS): Synthetic amorphous silica, precipitated

China: Synthetic amorphous silica, precipitated

Korea (TCCL): Synthetic amorphous silica, precipitated

Date of issue : 03/31/2005  
Authored by **KEMIKA**

Date of Revision : 11/14/2007

Philippines (RA6969): Synthetic amorphous silica, precipitated; Sodium metal.

## SiGNa™ NaK-Silica Gel (Stage I)

### Section 16. Other information

**Label Requirements:** CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS.  
SPILLAGE MAY CAUSE FIRE OR LIBERATE POISONOUS GAS.  
CONTACT WITH WATER MAY CAUSE FLASH FIRE.

**Hazardous Material  
Information System (USA):**

Health	3
Fire hazard	3
Reactivity	2
Personal protection	C

**National Fire Protection  
Association (USA):**



**References:** ANSI Z400.1, MSDS Standard, 2001. -Manufacturer's Material Safety Data Sheet. - 29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG.

**Date of Issue:** 03/31/2005

**Notice to Reader:**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Date of issue** : 03/31/2005  
Authored by **KEMIKA**

**Date of Revision** : 11/14/2007